

Safety data sheet

(EC) 1907/2006 (REACH), Annex II, as amended by Regulation (EU) 2021/848

Date of revision: 02.09.2022
Date of previous issue: 09.12.2020
Version number 5 (replaces version 4)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Normatop Clear Comp. A
- **UFI:** JG99-20NP-J00M-FNGG
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use** Coating
- **Application of the substance / the mixture**
2-comp. polyurethane paint, Comp. A
Uses in Coatings - Industrial use
Uses in Coatings - Professional use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Nor-Maali Oy
Vanhatie 20, 15240 Lahti, FINLAND
- **Further information obtainable from:** MSDS (Nor-Maali Oy) tel.+358 3 874 650, sds@nor-maali.fi
- **1.4 Emergency telephone number:** Contact National Poison Center

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

Product definition: mixture

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS02



GHS07

· **Signal word** Warning

· **Hazard-determining components of labelling:**

n-butyl acetate
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate
maleic anhydride
methyl methacrylate
2-hydroxyethyl methacrylate

(Contd. on page 2)

Trade name: Normatop Clear Comp. A

(Contd. of page 1)

Hazard statements

- H226 Flammable liquid and vapour.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P405 Store locked up.

2.3 Other hazards

Results of PBT and vPvB assessment

- PBT:** Not applicable.
- vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	25 - 50%
CAS: 128601-23-0 EC number: 918-668-5 Reg.nr.: 01-2119455851-35-	Hydrocarbons, C9, aromatics (< 0.1% benzene) Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	2.5 - 10%
CAS: 104810-48-2 ELINCS: 400-830-7 Reg.nr.: 01-0000015075-76-	reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) Aquatic Chronic 2, H411; Skin Sens. 1A, H317	1 - 2.5%
CAS: 1065336-91-5 EC number: 915-687-0 Reg.nr.: 01-2119491304-40-	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	< 0.8%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28-	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	< 0.2%
CAS: 868-77-9 EINECS: 212-782-2 Reg.nr.: 01-2119490169-29-	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	< 0.2%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A, H317: C \geq 0.001 %	< 0.0002%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Never give anything by mouth or induce vomiting to an unconscious person or a person who has convulsions.

(Contd. on page 3)

Trade name: Normatop Clear Comp. A

(Contd. of page 2)

- **After inhalation:**
Remove person exposed to excessive solvent concentrations to fresh air, keep patient warm and at rest. If breathing is irregular, call national emergency number, if needed start giving artificial respiration and seek medical advice.
- **After skin contact:**
Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- **After eye contact:**
Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- **After swallowing:**
If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.
- **Information for doctor:** Treatment according to symptoms.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Alcohol resistant foam, CO₂, powders, water spray.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
Evacuate people from danger area and deny access to area. Remove containers from danger area and try to cool containers which cannot be removed safely. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- **Protective equipment:** Compressed air respirator and protective clothing.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- **6.2 Environmental precautions:**
Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.
- **6.3 Methods and material for containment and cleaning up:**
Absorb liquid components with liquid-binding material (sand, peat or other absorbent material). Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust,

(Contd. on page 4)

Safety data sheet

(EC) 1907/2006 (REACH), Annex II, as amended by Regulation (EU) 2021/848

Date of revision: 02.09.2022
Date of previous issue: 09.12.2020
Version number 5 (replaces version 4)

Trade name: Normatop Clear Comp. A

(Contd. of page 3)

particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Information about fire - and explosion protection:

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in accordance with local regulations. Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. Keep away from: oxidising agents, strong alkalis, strong acids. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not empty into drains.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

HTP	Short-term value: 725 mg/m ³ , 150 ppm Long-term value: 240 mg/m ³ , 50 ppm
-----	--

80-62-6 methyl methacrylate

HTP	Short-term value: 210 mg/m ³ , 50 ppm Long-term value: 42 mg/m ³ , 10 ppm
-----	--

108-31-6 maleic anhydride

HTP	Long-term value: 0.41 mg/m ³ , 0.1 ppm Ceiling limit : 0.81 mg/m ³ , 0.2 ppm
-----	---

DNELs

123-86-4 n-butyl acetate

Dermal	DNEL 7 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL 480 mg/m ³ (Workers - Long-term systemic effects)

128601-23-0 Hydrocarbons, C9, aromatics (< 0.1% benzene)

Dermal	DNEL 25 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL 150 mg/m ³ (Workers - Long-term systemic effects)

104810-48-2 reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

Dermal	DNEL 250 µg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL 0.35 mg/m ³ (Workers - Long-term systemic effects)

1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate

Dermal	DNEL 1.8 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL 1.27 mg/m ³ (Workers - Long-term systemic effects)

80-62-6 methyl methacrylate

Dermal	DNEL 13.67 mg/kg bw/day (Workers - Long-term systemic effects)
--------	--

(Contd. on page 5)

Safety data sheet
(EC) 1907/2006 (REACH), Annex II, as amended by Regulation
(EU) 2021/848

Trade name: Normatop Clear Comp. A

(Contd. of page 4)

Inhalative	DNEL	1.5 mg/kg bw/day (Workers - Long-term local effects) 348.4 mg/m ³ (Workers - Long-term systemic effects) 208 mg/m ³ (Workers - Long-term local effects)
868-77-9 2-hydroxyethyl methacrylate		
Dermal	DNEL	1.3 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL	4.9 mg/m ³ (Workers - Long-term systemic effects)
108-31-6 maleic anhydride		
Dermal	DNEL	0.2 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL	0.081 mg/m ³ (Workers - Long-term systemic effects)
PNECs		
123-86-4 n-butyl acetate		
PNEC		0.18 mg/L (Freshwater) 0.018 mg/L (Marine water) 35.6 mg/L (Sewage treatment)
PNEC		0.981 mg/kg dwt (Fresh water sediment) 0.0981 mg/kg dwt (Marine water sediment) 0.0903 mg/kg dwt (Soil)
104810-48-2 reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)		
PNEC		10 - 100 mg/L (Sewage treatment)
PNEC		3.37 - 7.26 mg/kg dwt (Fresh water sediment) 0.337 - 0.726 mg/kg dwt (Marine water sediment)
PNEC		2 - 14.52 mg/kg (Soil)
PNEC		2.3 - 23 µg/L (Freshwater) 0.23 - 0.46 µg/L (Marine water)
1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate		
PNEC		1 mg/L (Sewage treatment)
PNEC		1.05 mg/kg dwt (Fresh water sediment) 0.11 mg/kg dwt (Marine water sediment)
PNEC		0.21 mg/kg (Soil)
PNEC		2.2 µg/L (Freshwater) 0.22 µg/L (Marine water)
80-62-6 methyl methacrylate		
PNEC		10 mg/L (Sewage treatment)
PNEC		10.2 mg/kg dwt (Fresh water sediment) 0.102 mg/kg dwt (Marine water sediment)
PNEC		1.48 mg/kg (Soil)
PNEC		940 µg/L (Freshwater) 94 µg/L (Marine water)
868-77-9 2-hydroxyethyl methacrylate		
PNEC		10 mg/L (Sewage treatment)
PNEC		3.79 mg/kg dwt (Fresh water sediment) 3.79 mg/kg dwt (Marine water sediment)
PNEC		0.476 mg/kg (Soil)
PNEC		482 µg/L (Freshwater) 482 µg/L (Marine water)
108-31-6 maleic anhydride		
PNEC		0.0379 - 0.075 mg/L (Freshwater)

(Contd. on page 6)

Trade name: Normatop Clear Comp. A

(Contd. of page 5)

	0.00379 - 0.0075 mg/L (Marine water)
	4.46 - 44.6 mg/L (Sewage treatment)
PNEC	0.06 - 0.296 mg/kg dwt (Fresh water sediment)
	0.006 - 0.0296 mg/kg dwt (Marine water sediment)
PNEC	6.67 mg/kg (Secondary Poisoning)
	0.01 - 0.0369 mg/kg (Soil)

Additional information:

The information is based on the valid lists at the time of manufacture (Finland 654/2020).

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the HTP, suitable respiratory protection must be worn.

Respiratory protection:

If ventilation is insufficient or if workers are exposed to concentrations above the exposure limit they must use half- or full mask with gas filter A (brown, organic substances), and when grinding P2 (Iib) -type dust filter. Mask with combined filter (gas & dust) A2-P2 must be used when spraying. In the continuous long-term work it is recommended to use motored air protector or separative protector (fresh air hood or compressed air hood or such).

Hand protection



Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Wear suitable gloves tested to EN374.

May be used, gloves(breakthrough time) 4 - 8 hours: butyl rubber, nitrile rubber

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

The eye flushing device should be located near the the paint work area.

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

124 - 128 °C (123-86-4 n-butyl acetate)

Flammability

Not applicable.

Lower and upper explosion limit

Lower:

1.2 Vol % (123-86-4 n-butyl acetate)

Upper:

7.5 Vol % (123-86-4 n-butyl acetate)

(Contd. on page 7)

Safety data sheet

(EC) 1907/2006 (REACH), Annex II, as amended by Regulation (EU) 2021/848

Date of revision: 02.09.2022
Date of previous issue: 09.12.2020
Version number 5 (replaces version 4)

Trade name: Normatop Clear Comp. A

(Contd. of page 6)

· Flash point:	27 °C
· Ignition temperature:	370 °C (123-86-4 n-butyl acetate)
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-butyl acetate)
· Density and/or relative density	
· Density at 20 °C:	1 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	
Flammable liquid and vapour.	
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No specific test data related to reactivity available for this product or its ingredients.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
In confined or poorly ventilated spaces solvent may form an explosive mixture with air.
- **10.3 Possibility of hazardous reactions**
Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 8)

Safety data sheet

(EC) 1907/2006 (REACH), Annex II, as amended by Regulation (EU) 2021/848

Date of revision: 02.09.2022
Date of previous issue: 09.12.2020
Version number 5 (replaces version 4)

Trade name: Normatop Clear Comp. A

(Contd. of page 7)

- **10.6 Hazardous decomposition products:**
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

• **LD/LC50 values relevant for classification:**

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (rat) (OECD 423)
Dermal	LD50	> 14,112 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	23.4 mg/l (rat) (OECD 403)

128601-23-0 Hydrocarbons, C9, aromatics (< 0.1% benzene)

Oral	LD50	3,492 mg/kg (rat)
Dermal	LD50	3,160 mg/kg (rabbit)
Inhalative	LC50/4 h	> 6,193 mg/l (rat)

104810-48-2 reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

Oral	LD50	> 5,000 mg/kg (rat)
Dermal	LD50	> 2,000 mg/kg (rat)

1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate

Oral	LD50	3,230 mg/kg (rat)
Dermal	LD50	3,170 mg/kg (rat)

80-62-6 methyl methacrylate

Oral	LD50	7,900 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	29.8 mg/l (rat)

868-77-9 2-hydroxyethyl methacrylate

Oral	LD50	5,564 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)

108-31-6 maleic anhydride

Oral	LD50	1,090 mg/kg (rat)
Dermal	LD50	2,620 mg/kg (rabbit)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

• **Other information (about experimental toxicology):**

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Swallowing may cause nausea, diarrhea, vomiting, gastro-intestinal irritation and chemical pneumonia.

(Contd. on page 9)

Trade name: Normatop Clear Comp. A

(Contd. of page 8)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

123-86-4 n-butyl acetate

72-h EC50	647.7 mg/L (Desmodesmus subspicatus)
48-h EC50	44 mg/L (Daphnia magna)
96-h LC50	18 mg/L (Pimephales promelas) (OECD 203)
NOEC	200 mg/L (Desmodesmus subspicatus)

128601-23-0 Hydrocarbons, C9, aromatics (< 0.1% benzene)

72-h EC50	0.29 - 0.42 mg/L (Algae)
96-h LL50	5.491 - 10 mg/L (Fish)
48-h EL50	3.2 - 9.586 mg/L (Daphnia magna)

104810-48-2 reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

72-h EC50	9 mg/L (Algae)
48-h EC50	4 mg/L (Daphnia magna)
96-h LC50	2.8 mg/L (Fish)

1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate

72-h EC50	0.42 - 1.68 mg/L (Algae)
96-h LC50	0.96 mg/L (Fish)

80-62-6 methyl methacrylate

72-h EC50	110 mg/L (Algae)
48-h EC50	48 mg/L (Daphnia magna)
96-h LC50	79 mg/L (Fish)

868-77-9 2-hydroxyethyl methacrylate

72-h EC50	836 mg/L (Algae)
48-h EC50	380 mg/L (Daphnia magna)
96-h LC50	100 mg/L (Fish)

108-31-6 maleic anhydride

72-h EC50	65.78 - 150 mg/L (Algae)
48-h EC50	42.81 - 330 mg/L (Daphnia magna)
96-h LC50	75 mg/L (Fish)

· **12.2 Persistence and degradability**

Biodegradation:

n-butyl acetate: 90 %, 28 d -> readily

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 10)

Trade name: Normatop Clear Comp. A

(Contd. of page 9)

- **12.7 Other adverse effects**
- **Remark:** Harmful to fish


SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
 Do not allow to enter drains or watercourses. Material and/or container must be disposed of as hazardous waste.

· European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

- **Uncleaned packaging:**
- **Recommendation:**
 Empty, dry paint containers (hole made to the bottom) should be taken to collection centres for metallic paint packages. If this collecting/recycling centre doesn't exist, containers can be taken to a local dump pit. For more information contact your local waste disposal authorities or paint deliverer.

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
· ADR, IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids.
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, <u>S</u> -E
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT, 3, III

Trade name: Normatop Clear Comp. A

(Contd. of page 10)

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
 FLAMMABLE LIQUIDS
 P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Contact:** Nor-Maali Oy, tel. +358 3 874 650 or sds@nor-maali.fi

· **Date of previous version:** 09.12.2020

· **Version number of previous version:** 4

· **Abbreviations and acronyms:**

- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B

(Contd. on page 12)

Safety data sheet
(EC) 1907/2006 (REACH), Annex II, as amended by Regulation
(EU) 2021/848

Page 12/12
Date of revision: 02.09.2022
Date of previous issue: 09.12.2020
Version number 5 (replaces version 4)

Trade name: Normatop Clear Comp. A

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
· *** Data compared to the previous version altered.**

(Contd. of page 11)

GB