





SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Norrapid 7
- **UFI:** 9FU2-S0EQ-K004-5YGR
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use** Coating
- **Application of the substance / the mixture**
 Alkyd top coat
 Uses in Coatings - Industrial use
 Uses in Coatings - Professional use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Nor-Maali Oy
 Vanhatie 20, 15240 Lahti, FINLAND
- **Further information obtainable from:** MSDS (Nor-Maali Oy) tel.+358 3 874 650, sds@nor-maali.fi
- **1.4 Emergency telephone number:** Contact National Poison Center

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 Product definition: mixture
- **Classification according to Regulation (EC) No 1272/2008**
- | | |
|---|-----------------------------------|
|  | GHS02 flame |
| Flam. Liq. 3 | H226 Flammable liquid and vapour. |
- | | |
|---|---|
|  | GHS07 |
| Skin Irrit. 2 | H315 Causes skin irritation. |
| Skin Sens. 1 | H317 May cause an allergic skin reaction. |
| Aquatic Chronic 3 | H412 Harmful to aquatic life with long lasting effects. |
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**
- | | |
|---|---|
|  |  |
| GHS02 | GHS07 |
- **Signal word** Warning
- **Hazard-determining components of labelling:**
 maleic anhydride
 Fatty acids, C14-18 and C16-18-unsatd., maleated
- **Hazard statements**
 H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Trade name: Norrapid 7

(Contd. of page 1)

- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P403+P235 Store in a well-ventilated place. Keep cool.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-	xylene Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25 - 50%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	2.5 - 10%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40-	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	< 0.8%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32-	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	< 0.4%
CAS: 85711-46-2 EINECS: 288-306-2 Reg.nr.: 01-2119976378-19-	Fatty acids, C14-18 and C16-18-unsatd., maleated Skin Irrit. 2, H315; Skin Sens. 1, H317	< 0.2%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	< 0.00135%

Additional information:

Contains: > 1 % TiO₂ (<10 µm)

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Never give anything by mouth or induce vomiting to an unconscious person or a person who has convulsions.

After inhalation:

Remove person exposed to excessive solvent concentrations to fresh air, keep patient warm and at rest. If breathing is irregular, call national emergency number, if needed start giving artificial respiration and seek medical advice.

After skin contact:

Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact:

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.

(Contd. on page 3)

Trade name: Norrapid 7

(Contd. of page 2)

- **After swallowing:**
 If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.
- **Information for doctor:** Treatment according to symptoms.
- **4.2 Most important symptoms and effects, both acute and delayed**
 No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Alcohol resistant foam, CO₂, powders, water spray.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
 Evacuate people from danger area and deny access to area. Remove containers from danger area and try to cool containers which cannot be removed safely. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- **Protective equipment:** Compressed air respirator and protective clothing.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- **6.2 Environmental precautions:**
 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.
- **6.3 Methods and material for containment and cleaning up:**
 Absorb liquid components with liquid-binding material (sand, peat or other absorbent material). Ensure adequate ventilation.
- **6.4 Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws.
 When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

(Contd. on page 4)

Trade name: Norrapid 7

(Contd. of page 3)

- **Information about fire - and explosion protection:**
 Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 Store in accordance with local regulations. Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. Keep away from: oxidising agents, strong alkalis, strong acids. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not empty into drains.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene

HTP	Short-term value: 440 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

100-41-4 ethylbenzene

HTP	Short-term value: 880 mg/m ³ , 200 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

108-31-6 maleic anhydride

HTP	Long-term value: 0.41 mg/m ³ , 0.1 ppm Ceiling limit m ³ , 0.2 ppm	: 0.81 mg/
-----	--	------------

· **DNELs**

1330-20-7 xylene

Dermal	DNEL	180 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL	211 mg/m ³ (Workers - Long-term systemic effects)

100-41-4 ethylbenzene

Dermal	DNEL	180 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL	77 mg/m ³ (Workers - Long-term systemic effects) 442 mg/m ³ (Workers - Long-term local effects)

7779-90-0 trizinc bis(orthophosphate)

Dermal	DNEL	83 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL	5 mg/m ³ (Workers - Long-term systemic effects)

1314-13-2 zinc oxide

Dermal	DNEL	83 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL	5 mg/m ³ (Workers - Long-term systemic effects)

85711-46-2 Fatty acids, C14-18 and C16-18-unsatd., maleated

Dermal	DNEL	3.33 mg/kg bw/day (Workers - Long-term systemic effects)
--------	------	--

108-31-6 maleic anhydride

Dermal	DNEL	0.2 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL	0.081 mg/m ³ (Workers - Long-term systemic effects)

· **PNECs**

1330-20-7 xylene

PNEC	6.58 mg/L (Sewage treatment)
PNEC	12.46 mg/kg dwt (Fresh water sediment) 12.46 mg/kg dwt (Marine water sediment)

(Contd. on page 5)

Safety data sheet
(EC) 1907/2006 (REACH), Annex II, as amended by Regulation
(EU) 2021/848

Trade name: Norrapid 7

(Contd. of page 4)

PNEC	2.31 mg/kg dwt (Soil) 327 µg/L (Freshwater) 327 µg/L (Marine water)
------	---

100-41-4 ethylbenzene

PNEC	0.1 mg/L (Freshwater) 0.01 - 0.1 mg/L (Marine water) 9.6 mg/L (Sewage treatment)
PNEC	13.7 mg/kg dwt (Fresh water sediment) 1.37 mg/kg dwt (Marine water sediment) 2.68 mg/kg dwt (Soil)
PNEC	20 mg/kg (Secondary Poisoning)

7779-90-0 trizinc bis(orthophosphate)

PNEC	117.8 mg/kg dwt (Fresh water sediment) 56.5 mg/kg dwt (Marine water sediment) 35.6 mg/kg dwt (Soil)
PNEC	20 µg/L (Freshwater) 6.1 µg/L (Marine water) 100 µg/L (Sewage treatment)

1314-13-2 zinc oxide

PNEC	117.8 mg/kg dwt (Fresh water sediment) 56.5 mg/kg dwt (Marine water sediment)
PNEC	35.6 mg/kg (Soil)
PNEC	20.6 µg/L (Freshwater) 6.1 µg/L (Marine water) 100 µg/L (Sewage treatment)

85711-46-2 Fatty acids, C14-18 and C16-18-unsatd., maleated

PNEC	100 mg/L (Sewage treatment)
------	-----------------------------

108-31-6 maleic anhydride

PNEC	0.0379 - 0.075 mg/L (Freshwater) 0.00379 - 0.0075 mg/L (Marine water) 4.46 - 44.6 mg/L (Sewage treatment)
PNEC	0.06 - 0.296 mg/kg dwt (Fresh water sediment) 0.006 - 0.0296 mg/kg dwt (Marine water sediment)
PNEC	6.67 mg/kg (Secondary Poisoning) 0.01 - 0.0369 mg/kg (Soil)

Ingredients with biological limit values:

1330-20-7 xylene

BMGV (Great Britain)	5.0 mmol/l creatinine Sampling time: post shift Parameter: methyl hippuric acid of urine
BNO (Finland)	5.0 mmol/l Näytteenottoajankohta: Työvuoron päätyttyä Parametri: virtsan metyylihippuurihappo

100-41-4 ethylbenzene

BMGV (Great Britain)	5.2 mmol/l creatinine Sampling time: post shift after working week or exposure period Parameter: mandelic acid of urine
BNO (Finland)	5.2 mmol/l Näytteenottoajankohta: Työvuoron päätyttyä työviikon tai altistumisjakson loputtua Parametri: virtsan mantelihappo


Additional information:


The information is based on the valid lists at the time of manufacture (Finland 654/2020).

(Contd. on page 6)

Trade name: Norrapid 7

(Contd. of page 5)

- **8.2 Exposure controls**
 - **Appropriate engineering controls** No further data; see item 7.
 - **Individual protection measures, such as personal protective equipment**
 - **General protective and hygienic measures:**
 Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the HTP, suitable respiratory protection must be worn.
 - **Respiratory protection:**
 If ventilation is insufficient or if workers are exposed to concentrations above the exposure limit they must use half- or full mask with gas filter A (brown, organic substances), and when grinding P2 (Iib) -type dust filter. Mask with combined filter (gas & dust) A2-P2 must be used when spraying. In the continuous long-term work it is recommended to use motored air protector or separative protector (fresh air hood or compressed air hood or such).
 - **Hand protection**
- 

Protective gloves
- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
 Wear suitable gloves tested to EN374.
 Recommended, gloves(breakthrough time) > 8 hours: nitrile rubber, 4H, Teflon
 May be used, gloves(breakthrough time) 4 - 8 hours: neoprene, PVC
 - **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
 - **Eye/face protection**
- 

Tightly sealed goggles
- The eye flushing device should be located near the the paint work area.
- **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** Colourful
- **Odour:** Strong
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** 136 °C (100-41-4 ethylbenzene)
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** 1.1 Vol % (1330-20-7 xylene)
- **Upper:** 7 Vol % (1330-20-7 xylene)
- **Flash point:** 24 °C
- **Ignition temperature:** 430 °C (100-41-4 ethylbenzene)
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity at 40 °C** > 20.5 mm²/s
- **Dynamic:** Not determined.
- **Solubility**
- **water:** Not miscible or difficult to mix.

(Contd. on page 7)

Trade name: Norrapid 7

(Contd. of page 6)

<ul style="list-style-type: none"> · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C: 6.7 - 8.2 hPa (1330-20-7 xylene) · Density and/or relative density · Density at 20 °C: 1.2 g/cm³ · Relative density Not determined. · Vapour density Not determined.
<ul style="list-style-type: none"> · 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Auto-ignition temperature: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. · Change in condition · Evaporation rate Not determined.
<ul style="list-style-type: none"> · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Flammable liquid and vapour. · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No specific test data related to reactivity available for this product or its ingredients.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
Keep away from oxidizing agents, strongly alkaline and strongly acidic materials.
- **10.6 Hazardous decomposition products:**
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 8)

Trade name: Norrapid 7

(Contd. of page 7)

LD/LC50 values relevant for classification:		
1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	4,300 mg/kg (rabbit)
Inhalative	LC50/4 h	20 mg/l (rat)
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
Inhalative	LC50/4 h	4,000 mg/l (rabbit)
7779-90-0 trizinc bis(orthophosphate)		
Oral	LD50	> 5,000 mg/kg (rat)
1314-13-2 zinc oxide		
Oral	LD50	> 5,000 mg/kg (rat)
Dermal	LD50	> 2,000 mg/kg (rat)
Inhalative	LC50/4 h	5,700 mg/l (rat)
85711-46-2 Fatty acids, C14-18 and C16-18-unsatd., maleated		
Oral	LD50	> 2,000 mg/kg (rat)
Dermal	LD50	> 2,000 mg/kg (rat)
108-31-6 maleic anhydride		
Oral	LD50	1,090 mg/kg (rat)
Dermal	LD50	2,620 mg/kg (rabbit)

- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Other information (about experimental toxicology):**
Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Swallowing may cause nausea, diarrhea, vomiting, gastro-intestinal irritation and chemical pneumonia.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Ethylbenzene may cause cancer to humans (carcinogenic, group 2B, IARC), but information available is insufficient for satisfactory estimate.
- **11.2 Information on other hazards**

Endocrine disrupting properties
None of the ingredients is listed.

Trade name: Norrapid 7

(Contd. of page 8)

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

1330-20-7 xylene

48-h EC50	165 mg/L (Daphnia magna)
96-h LC50	26.7 mg/L (Pimephales promelas)
48-h LC50	86 mg/L (Leuciscus idus melanotus)

100-41-4 ethylbenzene

48-h EC50	7.2 mg/L (Daphnia magna)
96-h LC50	4.2 mg/L (Oncorhynchus mykiss)

7779-90-0 trizinc bis(orthophosphate)

48-h EC50	> 2.34 mg/L (Daphnia magna)
96-h LC50	0.112 - 2.92 mg/L (Fish)
72-h IC50	0.136 - 0.15 mg/L (Algae)

1314-13-2 zinc oxide

96-h EC50	0.3 - 1.94 mg/L (Algae)
48-h EC50	155 - 100,000 ppm (Daphnia magna)
96-h LC50	112 - 8,062 ppm (Fish)

85711-46-2 Fatty acids, C14-18 and C16-18-unsatd., maleated

72-h EC50	2.76 - 100 mg/L (Algae)
48-h EC50	0.53 - 100 mg/L (Daphnia magna)
96-h LC50	1.17 - 100 mg/L (Fish)

108-31-6 maleic anhydride

72-h EC50	65.78 - 150 mg/L (Algae)
48-h EC50	42.81 - 330 mg/L (Daphnia magna)
96-h LC50	75 mg/L (Fish)

· **12.2 Persistence and degradability**

Biodegradability:

Xylene: readily

Ethylbenzene: readily

Trizinc bis(orthophosphate): not readily

· **12.3 Bioaccumulative potential**

Xylene: LogPow = 3,12 (low)

Ethylbenzene: LogPow = 3,15 (low)

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Remark:** Toxic for fish

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Do not allow to enter drains or watercourses. Material and/or container must be disposed of as hazardous waste.

· **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---


(Contd. on page 10)

Trade name: Norrapid 7

(Contd. of page 9)

- **Uncleaned packaging:**
- **Recommendation:**
 Empty, dry paint containers (hole made to the bottom) should be taken to collection centres for metallic paint packages. If this collecting/recycling centre doesn't exist, containers can be taken to a local dump pit. For more information contact your local waste disposal authorities or paint deliverer.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR, IMDG, IATA	PAINT
· 14.3 Transport hazard class(es) · ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number:	Warning: Flammable liquids. 30 F-E,S-E
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code	5L 3 D/E
· IMDG · Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Trade name: Norrapid 7

(Contd. of page 10)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

· **Contact:** Nor-Maali Oy, tel. +358 3 874 650 or sds@nor-maali.fi

· **Date of previous version:** 18.01.2021

· **Version number of previous version:** 7

· **Abbreviations and acronyms:**

- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Resp. Sens. 1: Respiratory sensitisation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1A: Skin sensitisation – Category 1A
- STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**