

**Safety data sheet**

(EC) 1907/2006 (REACH), Annex II, as amended by Regulation (EU) 2018/1480

Date of revision: 01.07.2020  
Date of previous issue: 01.03.2017  
Version number 4

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** OH 02 (alkydthinner)
  
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use** Coating
- **Application of the substance / the mixture**  
Thinner  
Uses in Coatings - Industrial use  
Uses in Coatings - Professional use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Nor-Maali Oy  
Vanhatie 20, 15240 Lahti, FINLAND
- **Further information obtainable from:** MSDS (Nor-Maali Oy) tel.+358 3 874 650, sds@nor-maali.fi
- **1.4 Emergency telephone number:** Contact National Poison Center

**SECTION 2: Hazards identification**

• **2.1 Classification of the substance or mixture**

Product definition: mixture

• **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1      H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4      H332 Harmful if inhaled.

STOT SE 3      H336 May cause drowsiness or dizziness.

• **2.2 Label elements**

• **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

• **Hazard pictograms**



GHS02



GHS07



GHS08



GHS09

• **Signal word** Danger

• **Hazard-determining components of labelling:**

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %)

**Trade name: OH 02 (alkydthinner)**

(Contd. of page 1)

- **Hazard statements**  
 H226 Flammable liquid and vapour.  
 H332 Harmful if inhaled.  
 H336 May cause drowsiness or dizziness.  
 H304 May be fatal if swallowed and enters airways.  
 H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P331 Do NOT induce vomiting.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- **Additional information:**  
 EUH066 Repeated exposure may cause skin dryness or cracking.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

EC number: 919-446-0 Reg.nr.: 01-2119458049-33-	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %) Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H332; STOT SE 3, H336	50 - 100%
--	---	-----------

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **General information:**  
 Never give anything by mouth or induce vomiting to an unconscious person or a person who has convulsions.
- **After inhalation:**  
 Remove person exposed to excessive solvent concentrations to fresh air, keep patient warm and at rest. If breathing is irregular, call national emergency number, if needed start giving artificial respiration and seek medical advice.
- **After skin contact:**  
 Remove contaminated clothing. Wash skin thoroughly with soap and water and apply skin cream.
- **After eye contact:**  
 Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- **After swallowing:**  
 If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.
- **4.2 Most important symptoms and effects, both acute and delayed**  
 No further relevant information available.
- **Information for doctor:** Treatment according to symptoms.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
 No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Alcohol resistant foam, CO<sub>2</sub>, powders, water spray.

(Contd. on page 3)

**Trade name: OH 02 (alkyld thinner)**

(Contd. of page 2)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**  
 Evacuate people from danger area and deny access to area. Remove containers from danger area and try to cool containers which cannot be removed safely. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- **Protective equipment:** Compressed air respirator and protective clothing.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
 No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- **6.2 Environmental precautions:**  
 Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- **6.3 Methods and material for containment and cleaning up:**  
 Absorb liquid components with liquid-binding material (sand, peat or other absorbent material). Ensure adequate ventilation.
- **6.4 Reference to other sections**  
 See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
 Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws.  
 When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
- **Information about fire - and explosion protection:**  
 Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
 Store in accordance with local regulations. Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. Keep away from: oxidising agents, strong alkalis, strong acids. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not empty into drains.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

(Contd. on page 4)

Trade name: OH 02 (alkydthinner)

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

**SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
 The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:**  
 The information is based on the valid lists at the time of manufacture (Finland 538/2018).
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
 Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the HTP, suitable respiratory protection must be worn.
- **Respiratory protection:**  
 If ventilation is insufficient or if workers are exposed to concentrations above the exposure limit they must use half- or full mask with gas filter A (brown, organic substances), and when grinding P2 (Ilb) -type dust filter. Mask with combined filter (gas & dust) A2-P2 must be used when spraying. In the continuous long-term work it is recommended to use motored air protector or separative protector (fresh air hood or compressed air hood or such).
- **Protection of hands:**



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- **Material of gloves**  
 Wear suitable gloves tested to EN374.  
 May be used, gloves(breakthrough time) 4 - 8 hours: butyl rubber, nitrile rubber
- **Penetration time of glove material**  
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

- The eye flushing device should be located near the the paint work area.
- **Body protection:** Protective work clothing

**SECTION 9: Physical and chemical properties**

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Fluid
Colour:	Colourless
Odour:	Strong
Odour threshold:	Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/freezing point:	Undetermined.
-------------------------------	---------------

(Contd. on page 5)

Trade name: OH 02 (alkyld thinner)

(Contd. of page 4)

<b>Initial boiling point and boiling range:</b> 151 - 200 °C	
· <b>Flash point:</b>	38.5 °C
· <b>Flammability (solid, gas):</b>	Not applicable.
· <b>Ignition temperature:</b>	> 200 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
Lower:	1 vol-%
Upper:	11 vol-%
· <b>Vapour pressure at 20 °C:</b>	2.31 hPa
· <b>Density at 20 °C:</b>	0.77 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic at 40 °C:	0.96 mm <sup>2</sup> /s
· <b>9.2 Other information</b>	No further relevant information available.

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No specific test data related to reactivity available for this product or its ingredients.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity**  
Harmful if inhaled.

· **LD/LC50 values relevant for classification:**

**Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %)**

Oral	LD50	> 15,000 mg/kg (rat)
Dermal	LD50	> 3,400 mg/kg (rat)
Inhalative	LC50/4 h	> 13.1 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Other information (about experimental toxicology):**  
Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by

(Contd. on page 6)

**Trade name: OH 02 (alkydhinner)**

(Contd. of page 5)

absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Swallowing may cause nausea, diarrhea, vomiting, gastro-intestinal irritation and chemical pneumonia.

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

**SECTION 12: Ecological information**

• **12.1 Toxicity**

• **Aquatic toxicity:**

**Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %)**

96-h LL50	10 - 30 mg/L (Oncorhynchus mykiss)
48-h EL50	10 - 22 mg/L (Daphnia magna)
72-h EL50	4.6 - 10 mg/L (Pseudokirchneriella subcapitata)

• **12.2 Persistence and degradability**

Biodegradation:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %): 74,7 % (28 d) -> readily

• **12.3 Bioaccumulative potential** No further relevant information available.

• **12.4 Mobility in soil** No further relevant information available.

• **Ecotoxicological effects:**

• **Remark:** Toxic for fish

• **12.5 Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

• **13.1 Waste treatment methods**

• **Recommendation**

Do not allow to enter drains or watercourses. Material and/or container must be disposed of as hazardous waste.

• **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---

• **Uncleaned packaging:**

• **Recommendation:**

Empty, dry paint containers (hole made to the bottom) should be taken to collection centres for metallic paint packages. If this collecting/recycling centre doesn't exist, containers can be taken to a local dump pit. For more information contact your local waste disposal authorities or paint deliverer.

**SECTION 14: Transport information**

• **14.1 UN-Number**



• **ADR, IMDG, IATA**

UN1263

(Contd. on page 7)

Trade name: OH 02 (alkyld thinner)

(Contd. of page 6)

<ul style="list-style-type: none"> <li>· 14.2 UN proper shipping name</li> <li>· ADR</li> <li>· IMDG</li> <li>· IATA</li> </ul>	PAINT RELATED MATERIAL, ENVIRONMENTALLY HAZARDOUS PAINT RELATED MATERIAL, MARINE POLLUTANT Marine Pollutant Chemical: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %) PAINT RELATED MATERIAL
<ul style="list-style-type: none"> <li>· 14.3 Transport hazard class(es)</li> <li>· ADR, IMDG</li> </ul>	
<ul style="list-style-type: none"> <li>· Class</li> </ul>	3 Flammable liquids.
<ul style="list-style-type: none"> <li>· IATA</li> </ul>	
<ul style="list-style-type: none"> <li>· Class</li> </ul>	3 Flammable liquids.
<ul style="list-style-type: none"> <li>· 14.4 Packing group</li> <li>· ADR, IMDG, IATA</li> </ul>	III
<ul style="list-style-type: none"> <li>· 14.5 Environmental hazards:</li> <li>· Marine pollutant:</li> <li>· Special marking (ADR):</li> </ul>	Product contains environmentally hazardous substances: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %) Yes Symbol (fish and tree)
<ul style="list-style-type: none"> <li>· 14.6 Special precautions for user</li> </ul>	Warning: Flammable liquids.
<ul style="list-style-type: none"> <li>· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· Transport/Additional information:</li> </ul>	
<ul style="list-style-type: none"> <li>· ADR</li> <li>· Limited quantities (LQ)</li> <li>· Transport category</li> <li>· Tunnel restriction code</li> </ul>	5L 3 D/E
<ul style="list-style-type: none"> <li>· IMDG</li> <li>· Limited quantities (LQ)</li> </ul>	EMS number: F-E, S-E 5L
<ul style="list-style-type: none"> <li>· UN "Model Regulation":</li> </ul>	UN1263, PAINT RELATED MATERIAL, ENVIRONMENTALLY HAZARDOUS, 3, III

**SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category  
 FLAMMABLE LIQUIDS  
 E2 Hazardous to the Aquatic Environment  
 P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 8)

Trade name: OH 02 (alkydthinner)

(Contd. of page 7)

- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· **Contact:** Nor-Maali Oy, tel. +358 3 874 650 or sds@nor-maali.fi

· **Abbreviations and acronyms:**

- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity - inhalation – Category 4
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· **\* Data compared to the previous version altered.**