

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** OH 13
- **UFI:** HKDQ-30EC-Y001-93J7
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use** Coating
- **Application of the substance / the mixture**
 Thinner
 Uses in Coatings - Industrial use
 Uses in Coatings - Professional use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Nor-Maali Oy
 Vanhatie 20, 15240 Lahti, FINLAND
- **Further information obtainable from:** MSDS (Nor-Maali Oy) tel.+358 3 874 650, sds@nor-maali.fi
- **1.4 Emergency telephone number:** Contact National Poison Center

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 Product definition: mixture
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02

- **Signal word** Danger
- **Hazard statements**
 H225 Highly flammable liquid and vapour.
- **Precautionary statements**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P403+P235 Store in a well-ventilated place. Keep cool.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

Determination of endocrine-disrupting properties

78-93-3 butanone

List II

Trade name: OH 13

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-	ethanol Flam. Liq. 2, H225	50 - 98%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	1 - 2.5%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	1 - 2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Never give anything by mouth or induce vomiting to an unconscious person or a person who has convulsions.

· **After inhalation:**

Remove person exposed to excessive solvent concentrations to fresh air, keep patient warm and at rest. If breathing is irregular, call national emergency number, if needed start giving artificial respiration and seek medical advice.

· **After skin contact:**

Remove contaminated clothing. Wash skin thoroughly with soap and water and apply skin cream.

· **After eye contact:**

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.

· **After swallowing:**

If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

· **Information for doctor:** Treatment according to symptoms.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** Alcohol resistant foam, CO₂, powders, water spray.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· **5.3 Advice for firefighters**

Evacuate people from danger area and deny access to area. Remove containers from danger area and try to cool containers which cannot be removed safely.

· **Protective equipment:** Compressed air respirator and protective clothing.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation.

Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

(Contd. on page 3)

Trade name: OH 13

(Contd. of page 2)

- **6.2 Environmental precautions:**
 Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- **6.3 Methods and material for containment and cleaning up:**
 Absorb liquid components with liquid-binding material (sand, peat or other absorbent material).
 Ensure adequate ventilation.
- **6.4 Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws.
 When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
- **Information about fire - and explosion protection:**
 Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 Store in accordance with local regulations. Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. Keep away from: oxidising agents, strong alkalis, strong acids. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not empty into drains.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

64-17-5 ethanol	
HTP	Short-term value: 2500 mg/m ³ , 1300 ppm Long-term value: 1900 mg/m ³ , 1000 ppm
67-63-0 propan-2-ol	
HTP	Short-term value: 620 mg/m ³ , 250 ppm Long-term value: 500 mg/m ³ , 200 ppm
78-93-3 butanone	
HTP	Short-term value: 300 mg/m ³ , 100 ppm Long-term value: 60 mg/m ³ , 20 ppm skin

(Contd. on page 4)

Trade name: OH 13

(Contd. of page 3)

· DNELs	
64-17-5 ethanol	
Dermal	DNEL 343 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL 950 mg/m3 (Workers - Long-term systemic effects)
67-63-0 propan-2-ol	
Dermal	DNEL 888 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL 500 mg/m3 (Workers - Long-term systemic effects)
78-93-3 butanone	
Dermal	DNEL 1,161 mg/kg bw/day (Workers - Long-term systemic effects)
Inhalative	DNEL 600 mg/m3 (Workers - Long-term systemic effects)
· PNECs	
64-17-5 ethanol	
PNEC	0.96 mg/L (Freshwater) 0.79 mg/L (Marine water) 580 mg/L (Sewage treatment)
PNEC	3.6 mg/kg dwt (Fresh water sediment) 2.9 mg/kg dwt (Marine water sediment)
PNEC	380 - 720 mg/kg (Secondary Poisoning) 0.63 mg/kg (Soil)
67-63-0 propan-2-ol	
PNEC	140.9 mg/L (Freshwater) 140.9 mg/L (Marine water) 2,251 mg/L (Sewage treatment)
PNEC	552 mg/kg dwt (Fresh water sediment) 552 mg/kg dwt (Marine water sediment)
PNEC	160 mg/kg (Secondary Poisoning) 28 mg/kg (Soil)
78-93-3 butanone	
PNEC	55.8 mg/L (Freshwater) 55.8 mg/L (Marine water) 709 mg/L (Sewage treatment)
PNEC	284.74 mg/kg dwt (Fresh water sediment) 284.7 mg/kg dwt (Marine water sediment)
PNEC	1,000 mg/kg (Secondary Poisoning) 22.5 mg/kg (Soil)

· Additional information:

The information is based on the valid lists at the time of manufacture (Finland 654/2020).

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the HTP, suitable respiratory protection must be worn.

· Respiratory protection:

If ventilation is insufficient or if workers are exposed to concentrations above the exposure limit they must use half- or full mask with gas filter A (brown, organic substances), and when grinding P2 (Ib) -type dust filter. Mask with combined filter (gas & dust) A2-P2 must be used when spraying. In the continuous long-term work it is recommended to use motored air protector or separative protector (fresh air hood or compressed air hood or such).

(Contd. on page 5)

Trade name: OH 13

(Contd. of page 4)

· **Hand protection**



Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Wear suitable gloves tested to EN374.

May be used, gloves(breakthrough time) 4 - 8 hours: butyl rubber, nitrile rubber

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed goggles

The eye flushing device should be located near the the paint work area.

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	-114.5 °C
· Boiling point or initial boiling point and boiling range	78 °C (64-17-5 ethanol)
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	3.5 Vol % (64-17-5 ethanol)
· Upper:	15 Vol % (64-17-5 ethanol)
· Flash point:	< 23 °C
· Ignition temperature:	425 °C (64-17-5 ethanol)
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	1.2 mPas
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	59 hPa (64-17-5 ethanol)
· Density and/or relative density	
· Density at 20 °C:	0.8 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· **9.2 Other information**

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.

(Contd. on page 6)

Trade name: OH 13

(Contd. of page 5)

· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	
Highly flammable liquid and vapour.	
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No specific test data related to reactivity available for this product or its ingredients.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- **10.4 Conditions to avoid**
Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

64-17-5 ethanol		
Oral	LD50	8,300 mg/kg (mouse)
Dermal	LD50	17,100 mg/kg (rabbit)
Inhalative	LC50/4 h	117 - 125 mg/l (rat)
67-63-0 propan-2-ol		
Oral	LD50	5,840 mg/kg (rat)
78-93-3 butanone		
Oral	LD50	> 2,000 mg/kg (rat)
Dermal	LD50	> 5,000 mg/kg (rabbit)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Trade name: OH 13

(Contd. of page 6)

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Other information (about experimental toxicology):**
 Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Swallowing may cause nausea, diarrhea, vomiting, gastro-intestinal irritation and chemical pneumonia.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

78-93-3	butanone	List II
---------	----------	---------

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

64-17-5 ethanol

72-h EC50	275 mg/L (Algae)
48-h EC50	10 mg/L (Daphnia magna)
96-h LC50	14.2 - 15.4 mg/L (Fish)

67-63-0 propan-2-ol

96-h LC50	9,640 - 10,000 mg/L (Fish)
24-h EC50	10,000 mg/L (Daphnia magna)

78-93-3 butanone

48-h EC50	308 - 5,091 mg/L (Daphnia magna)
96-h LC50	2.993 - 3.2 mg/L (Fish)
96-h EC50	2,029 mg/L (Algae)

· **12.2 Persistence and degradability**

Biodegradability:
 Ethanol: over 80%, 4 d (OECD TG 301)
 butanone: readily

· **12.3 Bioaccumulative potential** Ethanol: LogPow = -0,35 (low)

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Do not allow to enter drains or watercourses. Material and/or container must be disposed of as hazardous waste.

(Contd. on page 8)

Trade name: OH 13

(Contd. of page 7)

· **European waste catalogue**

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

· **Uncleaned packaging:**

· **Recommendation:**

Empty, dry paint containers (hole made to the bottom) should be taken to collection centres for metallic paint packages. If this collecting/recycling centre doesn't exist, containers can be taken to a local dump pit. For more information contact your local waste disposal authorities or paint deliverer.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN1263

· **14.2 UN proper shipping name**

· **ADR, IMDG, IATA** PAINT RELATED MATERIAL

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class** 3 Flammable liquids.

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):** 33

· **EMS Number:** F-E,S-E

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 5L

· **Transport category** 2

· **Tunnel restriction code** D/E

· **IMDG**

· **Limited quantities (LQ)** 5L

· **UN "Model Regulation":** UN 1263 PAINT RELATED MATERIAL, 3, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

FLAMMABLE LIQUIDS

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

(Contd. on page 9)

Trade name: OH 13

(Contd. of page 8)

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

78-93-3 butanone

3

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

78-93-3 butanone

3

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Contact:** Nor-Maali Oy, tel. +358 3 874 650 or sds@nor-maali.fi

· **Date of previous version:** 31.12.2020

· **Version number of previous version:** 7

· **Abbreviations and acronyms:**

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**