

WATER-BORNE SEMI GLOSS ACRYLIC COATING

DIRECT-TO-METAL

TOPCOAT

PRIMER

AKVANOR 100 SG

Environmentally friendly acrylic coating for machinery and equipment

When a stylish surface is required for your product, **Akvanor 100 SG** is the right choice. This easy to use direct-to-metal acrylic coating offers environmentally friendly corrosion resistance in industrial sites.

WHY TO CHOOSE AKVANOR 100 SG?



USER FRIENDLY PRODUCT

One-component product,
easy to spray.



GREENER CHOICE

Water-borne option to
enhance work safety.



FAST THROUGHPUT

As a direct-to-metal
coating, only one layer is
required, which speeds up
the production.



CORROSION PROTECTION

Corrosion-resistant direct-
to-metal acrylic coating.

NORMAALI



+358 (0) 3 874 650



sales@nor-maali.fi



Vanhatie 20
15240 Lahti, Finland



Nor-maali.fi

FAST, EASY AND SAFER PAINTING

Akvanor 100 SG as a water-borne acrylic coating reduces exposure to hazardous substances and significantly reduces the risk of explosion in paint shops. Since water-borne coatings evaporate mainly water into the air, Akvanor 100 SG is also an environmentally friendly choice thanks to its low VOC content.

Fast throughput and semi gloss finish

As a one-component product, Akvanor 100 SG is very easy to use. With this direct-to-metal coating finished surface is ready with one layer, which speeds up the production lead time. The result is smooth and semi gloss surface that looks stylish in machines and equipment.

Approvals

Akvanor 100 SG has been tested according to standard ACT Volvo STD 423-0014 (rev. 6) and it fulfils the requirements.

Quality system approval according to Marine Equipment Directive 2014/90/EU



Updated Technical Data Sheet (TDS) and Safety Data Sheet (SDS) and our general conditions of sales are available at www.nor-maali.fi. In case of differences in information: the order of priority of information is TDS and SDS over any other information.



AKVANOR 100 SG

GENERAL STEEL STRUCTURES MACHINERY AND EQUIPMENT

EASY TO USE ENVIRONMENTALLY FRIENDLY

VOLUME SOLIDS	49 %
VOC	40 G/L
COLOURS	RAL AND NCS S
FINISH	SEMI GLOSS
CORROSIVITY CATEGORY	
SINGLE-COAT	C2 – C3
DURABILITY RANGE	120 µm – C3 M

More information in the TDS

NORMAALI

ESTONIA

Oü Nor-Maali
Vana-Narva mnt 5c,
Maardu
74114 Estonia

Tel. +372 600 3948
tellimus@nor-maali.ee

SLOVAKIA

Nor-Maali s.r.o.
Senecká cesta 18
821 04 Bratislava

Tel. +421 903 210 259
sales@nor-maali.sk

SWEDEN

Nor-Maali Group AB
Varggatan 23
749 40 Enköping

Tel. +46 70 537 6404
Tel. +46 70 537 6414
forsaljning@normaali.se