

NORECOAT HS PRIMER

High solids epoxy primer for more environmentally friendly painting process

When VOC-emissions must be reduced, **NorECOat HS Primer** is the right choice. This epoxy primer based on renewable natural materials offers a cost effective painting process even at lower temperatures.

WHY TO CHOOSE NORECOAT HS PRIMER?



EXCELLENT CORROSION RESISTANCE

Epoxy primer protects against corrosion.



FAST DRYING

A fast overcoating interval enables fast, cost effective production.



CURES AT LOW TEMPERATURES

The product can be painted down to +5°C.



GREENER CHOICE

Technology of the high solids NorECOat HS Primer is based on renewable natural materials.

NORMAALI



+358 (0) 3 874 650



sales@nor-maali.fi



Vanhatie 20
15240 Lahti, Finland



Nor-maali.fi

CORROSION PROTECTION COST-EFFECTIVELY

Thanks to its raw material composition, NorECOat HS Primer provides excellent protection against corrosion. As a fast-drying epoxy primer, it also speeds up production.

Cures also at low temperatures

NorECOat HS Primer can also be used at lower temperatures as it cures down to +5°C. Low temperature is not an obstacle for spraying.

Cost effective painting process

NorECOat HS Primer dries quickly. It can be recoated with paints of the same type after 2 hours and with polyurethane paints after 3 hours. The painting process speeds up significantly.

A greener choice

Technology of the high solids NorECOat HS Primer is based on renewable natural materials. Low VOC-content guarantees a safer painting process for both the user and the environment.

Updated Technical Data Sheet (TDS) and Safety Data Sheet (SDS) and our general conditions of sales are available at www.nor-maali.fi. In case of differences in information: the order of priority of information is TDS and SDS over any other information.



NORECOAT HS PRIMER

GENERAL STEEL STRUCTURES MACHINERY AND EQUIPMENT

DRIES QUICKLY EVEN AT LOW TEMPERATURES

| | |
|-----------------------------|-----------|
| VOLUME SOLIDS | 78 % |
| VOC | 190 G/L |
| MIXING RATIO | 5:1 |
| POT-LIFE | 1 H |
| COLOURS | GREY |
| FINISH | SEMI MATT |
| CORROSIVITY CATEGORY | |
| PRIMER | C2 – C5 |

More information in the TDS



ESTONIA

Oü Nor-Maali
Vana-Narva mnt 5c,
Maardu
74114 Estonia

Tel. +372 600 3948
tellimus@nor-maali.ee

SLOVAKIA

Nor-Maali s.r.o.
Senecká cesta 18
821 04 Bratislava

Tel. +421 903 210 259
sales@nor-maali.sk

SWEDEN

Nor-Maali Group AB
Varggatan 23
749 40 Enköping

Tel. +46 70 537 6404
Tel. +46 70 537 6414
forsaljning@normaali.se