

WATER-BORNE SEMI GLOSS EPOXY COATING

DIRECT-TO-METAL

TOPCOAT

PRIMER

NOREPOX AQUA DTM

Environmentally friendly water-borne epoxy coating for challenging conditions

When a high resistant surface is required, **Norepox Aqua DTM** is the right choice. This hard surface epoxy coating offers environmentally friendly corrosion resistance even in challenging industrial sites where the criteria for durability are high.

WHY TO CHOOSE NOREPOX AQUA DTM?



GREENER CHOICE

Water-borne option to enhance work safety.



SUPERIOR DURABILITY

Hard and durable surface. Excellent corrosion resistance.



USER FRIENDLY PRODUCT

Excellent spraying properties. Smooth and stylish surface without dry spray.



FAST DRYING

Dries fast and is soon ready for packing even at lower temperatures.

NORMAALI



+358 (0) 3 874 650



sales@nor-maali.fi



Vanhatie 20
15240 Lahti, Finland



Nor-maali.fi

DURABLE AND GREENER CHOICE

Thanks to its durable surface, Norepox Aqua DTM provides excellent protection against mechanical stress and corrosion. This direct-to-metal epoxy coating also contains all the benefits of a water-borne coating: Norepox Aqua DTM e.g. reduces exposure to hazardous substances and significantly reduces the risk of explosion in paint shops. Thanks to its low VOC content, it is also an environmentally friendly choice.

Superior end-result and fast throughput

The spraying properties of Norepox Aqua DTM are unique. The spray fan is really uniform and forming of dry spray is minimal. The painted surface is always smooth and stylish looking. Norepox Aqua DTM dries quickly, even at lower temperatures.

It's time to lower the VOCs

We are constantly developing more environmentally friendly products, which are as excellent in technical properties as their solvent-based counterparts. Since water-borne coatings evaporate mainly water into the air, they are clearly a greener choice.

Updated Technical Data Sheet (TDS) and Safety Data Sheet (SDS) and our general conditions of sales are available at www.nor-maali.fi. In case of differences in information: the order of priority of information is TDS and SDS over any other information.



NOREPOX AQUA DTM

GENERAL STEEL STRUCTURES MACHINERY AND EQUIPMENT

EXCELLENT SPRAYING PROPERTIES CORROSION RESISTANT

VOLUME SOLIDS	50 %
VOC	62 G/L
MIXING RATIO	4:1
POT-LIFE	1.5 H
COLOURS	RAL AND NCS S
FINISH	SEMI GLOSS
CORROSION CATEGORY	
SINGLE-COAT	C2 – C3
DURABILITY RANGE	120 µm – C3 M
PAINT SYSTEMS	C4 – C5

More information in the TDS



ESTONIA

Oü Nor-Maali
Vana-Narva mnt 5c,
Maardu
74114 Estonia

Tel. +372 600 3948
tellimus@nor-maali.ee

RUSSIA

ООО «НОР-МААЛИ»
Псковская обл., Псковский р-н
СП «Тямшанская волость»
ОЭЗ ППТ «Моглино», Россия

Tel. +7 812 600 4949
info@nor-maali.ru

SLOVAKIA

Nor-Maali s.r.o.
Senecká cesta 18
821 04 Bratislava

Tel. +421 903 210 259
sales@nor-maali.sk

SWEDEN

Nor-Maali Group AB
Varggatan 23
749 40 Enköping

Tel. +46 70 537 6404
Tel. +46 70 537 6414
forsaljning@normaali.se