

SOLVENT-BASED SEMI GLOSS POLYURETHANE COATING

DIRECT-TO-METAL

TOPCOAT

NORMAFINE 40 HS

High solids polyurethane coating for cost-effective painting

When industrial sites require a durable surface, **Normafine 40 HS** is the right choice. This high solids acrylic polyurethane topcoat and direct-to-metal coating enables fast, cost-effective painting process.

WHY TO CHOOSE NORMAFINE 40 HS?



COST-EFFECTIVE PAINTING

Fast painting process with high solids direct-to-metal coating.



EASY TO SPRAY

Thick films (160 µm DFT) are also possible.



WEATHER RESISTANT

UV-resistant acrylic polyurethane coating.



DURABLE SURFACE

Corrosion-resistant direct-to-metal coating.

NORMAALI



+358 (0) 3 874 650



sales@nor-maali.fi



Vanhatie 20
15240 Lahti, Finland



Nor-maali.fi

SUSTAINABLE SURFACE COST- EFFECTIVELY

Thanks to its durable surface, Normafine 40 HS protects against UV radiation and corrosion. As a high solids polyurethane coating, it is also a more environmentally friendly choice.

Semi gloss finish for all-around use

Used as a direct-to-metal coating, Normafine 40 HS offers a stylish surface in just one coat.

Cost effective painting

High solids Normafine 40 HS can be used to spray thick films in one painting. The product is very competitive in terms of price per square meter.

Protects against UV and corrosion

Normafine 40 HS can be used in corrosivity categories C2 and C3 as a single-coat. In higher corrosivity categories, it can be used as a topcoat. As an acrylic polyurethane coating, it also provides weather resistance.

Updated Technical Data Sheet (TDS) and Safety Data Sheet (SDS) and our general conditions of sales are available at www.nor-maali.fi. In case of differences in information: the order of priority of information is TDS and SDS over any other information.



NORMAFINE 40 HS

GENERAL STEEL STRUCTURES MACHINERY AND EQUIPMENT

PROTECTS AGAINST UV AND CORROSION

VOLUME SOLIDS	66 %
VOC	300 G/L
MIXING RATIO	9:1
POT-LIFE	1 H 30 MIN
COLOURS	RAL AND NCS S
FINISH	SEMI GLOSS
CORROSIVITY CATEGORY	
SINGLE-COAT	C2 – C3
TOPCOAT	C3 – C5

More information in the TDS



ESTONIA

Oü Nor-Maali
Vana-Narva mnt 5c,
Maardu
74114 Estonia

Tel. +372 600 3948
tellimus@nor-maali.ee

SLOVAKIA

Nor-Maali s.r.o.
Senecká cesta 18
821 04 Bratislava

Tel. +421 903 210 259
sales@nor-maali.sk

SWEDEN

Nor-Maali Group AB
Varggatan 23
749 40 Enköping

Tel. +46 70 537 6404
Tel. +46 70 537 6414
forsaljning@normaali.se