More environmentally friendly high solids polyurethane coating

When challenging industrial sites require a high durable surface,

Normafine 80 is the right choice. This high solids glossy acrylic

polyurethane topcoat and single-coat enables cost-effective painting

with environment in mind.

WHY TO CHOOSE NORMAFINE 80?



SUPERIOR DURABILITY

Hard surface corrosion resistant direct-to-metal coating.



WEATHER RESISTANT

Excellent UV-resistance.



STYLISH END-RESULT

Glossy and smooth finish.



GREENER CHOICE

No solvents defined as HAPS or environmentally toxic zinc.







sales@nor-maali.fi





DURABLE FINISH COST-EFFECTIVELY

Thanks to its durable surface, Normafine 80 provides excellent protection against UV radiation and corrosion. As a high solids acrylic polyurethane coating, it is also a more environmentally friendly choice.

Superior end-result with just one layer of paint

Used as a direct-to-metal coating, Normafine 80 offers a stylish finish in just one coat. This fast-drying, cost-effective product enables a fast painting process.

A greener choice

Normafine 80, a high solids coating, doesn't contain solvents defined as HAPS or environmentally toxic zinc. From solvent-based coatings, it is clearly a safer option for both the user and the environment.

It's time to lower the VOCs

We are constantly developing more environmentally friendly products, which include solvent-based high solids products. By reducing the amount of solvents and changing the quality of solvents and other raw materials, we are able to offer greener and safer products.

Updated Technical Data Sheet (TDS) and Safety Data Sheet (SDS) and our general conditions of sales are available at www.nor-maali.fi. In case of differences in information: the order of priority of information is TDS and SDS over any other information.



NORMAFINE 80

MACHINERY AND EQUIPMENT GENERAL STEEL STRUCTURES STORAGE TANKS

CORROSION RESISTANT GLOSS RETAINING COATING

VOLUME SOLIDS	70 %
VOC	260 G/L
MIXING RATIO	5:1
POT-LIFE	1 H 15 MIN
COLOURS	RAL, NCS S, KY AND SSG
FINISH	GLOSSY
CORROSIVITY CATEGORY	
SINGLE-COAT	C2 – C3
DURABILITY RANGE	120 µm – C3 M
TOPCOAT	C4 – C5

More information in the TDS



ESTONIA

Oü Nor-Maali Vana-Narva mnt 5c, Maardu 74114 Estonia

Tel. +372 600 3948 tellimus@nor-maali.ee

SLOVAKIA

Nor-Maali s.r.o. Senecká cesta 18 821 04 Bratislava

Tel. +421 903 210 259 sales@nor-maali.sk

SWEDEN

Nor-Maali Group AB Varggatan 23 749 40 Enköping

Tel. +46 70 537 6404 Tel. +46 70 537 6414 forsaljning@normaali.se