

SOLVENT-BASED HIGH GLOSS POLYURETANE COATING

DIRECT-TO-METAL

TOP COAT

NORMAFINE HS

High gloss polyurethane coating for demanding applications

When challenging industrial sites require a high durable surface, **Normafine HS** is the right choice. This high solids acrylic polyurethane topcoat and single-coat offers a perfect, high gloss finish to the painted object with environment in mind.

WHY TO CHOOSE NORMAFINE HS?



SUPERIOR DURABILITY

Hard surface corrosion resistant direct-to-metal coating.



WEATHER RESISTANT

Excellent colour and gloss retention.



STYLISH END-RESULT

High gloss surface for demanding ACE & OEM applications.



GREENER CHOICE

High solids Normafine HS doesn't contain environmentally toxic zinc.

NORMAALI



+358 (0) 3 874 650



sales@nor-maali.fi



Vanhatie 20
15240 Lahti, Finland



Nor-maali.fi

ENVIRONMENTALLY FRIENDLY HIGH GLOSS SURFACE

Thanks to its durable surface, Normafine HS provides excellent protection against UV radiation and corrosion. As a high solids acrylic polyurethane coating, it is also a more environmentally friendly choice.

Superior high gloss end-result with just one layer of paint

Used as a direct-to-metal, Normafine HS offers a stylish, high gloss finish in just one coat. The objects to be painted get a full-bodied surface. Normafine HS enables a fast painting process, as objects are quickly movable.

A greener choice

Normafine HS, a high solids coating, doesn't contain environmentally toxic zinc. From solvent-based coatings, it is a safer option for both the user and the environment.

It's time to lower the VOCs

We are constantly developing more environmentally friendly products, which include solvent-based high solids products. By reducing the amount of solvents and changing the quality of solvents and other raw materials, we are able to offer greener and safer products.

Updated Technical Data Sheet (TDS) and Safety Data Sheet (SDS) and our general conditions of sales are available at www.nor-maali.fi. In case of differences in information: the order of priority of information is TDS and SDS over any other information.



NORMAFINE HS

MACHINERY AND EQUIPMENT

CORROSION RESISTANT GLOSS RETAINING COATING

VOLUME SOLIDS	70 %
VOC	270 G/L
MIXING RATIO	4:1
POT-LIFE	45 MIN
COLOURS	RAL, NCS S, KY AND SSG
FINISH	HIGH GLOSS
CORROSIVITY CATEGORY	
SINGLE-COAT	C2 – C3
DURABILITY RANGE	120 µm – C3 M
TOPCOAT	C4 – C5

More information in the TDS



ESTONIA

Oü Nor-Maali
Vana-Narva mnt 5c,
Maardu
74114 Estonia

Tel. +372 600 3948
tellimus@nor-maali.ee

SLOVAKIA

Nor-Maali s.r.o.
Senecká cesta 18
821 04 Bratislava

Tel. +421 903 210 259
sales@nor-maali.sk

SWEDEN

Nor-Maali Group AB
Varggatan 23
749 40 Enköping

Tel. +46 70 537 6404
Tel. +46 70 537 6414
forsaljning@normaali.se