

SEMI GLOSS ISOCYANATE FREE ACRYLIC COATING

DIRECT-TO-METAL

TOPCOAT

# NORECRYL 50

## User friendly weather resistant direct-to-metal NISO coating for demanding conditions

When a superior corrosion resistance is required of a coating, **Norecyl 50** is the right choice. This isocyanate-free acrylic topcoat and single-coat enables a safer anticorrosion painting process for the user.

### WHY TO CHOOSE NORECRYL 50?



#### SUPERIOR DURABILITY

Hard and durable surface,  
superior corrosion  
resistance.



#### SAFER CHOICE

Isocyanate-free.



#### LONG POT-LIFE

Simplifies the painting  
process.



#### STYLISH END-RESULT

Semi gloss and smooth  
surface.

**NOR**MAALI



+358 (0) 3 874 650



[sales@nor-maali.fi](mailto:sales@nor-maali.fi)



Vanhatie 20  
15240 Lahti, Finland



[Nor-maali.fi](http://Nor-maali.fi)

# CORROSION RESISTANCE WITHOUT ISOCYANATE

Thanks to its hard and durable surface, Norecyl 50 provides excellent protection against corrosion. As a high solids isocyanate-free coating, it is also a safer choice for the user.

## Superior durability

Thanks to its outstanding corrosion resistance and moderate weather resistance, it is suitable for both indoor and outdoor applications. As a single-coat, Norecyl 50 achieves corrosion class C4 M with 120 µm DFT.

## User-friendly option

Norecyl 50 doesn't contain isocyanate, making it a safer choice for the user. The coating has a long 3.5-hour pot-life, which offers flexibility for the painting process.

## High quality end-result with just one layer of coating

Direct-to-metal coating Norecyl 50 offers a stylish surface in just one layer of coating. Elevated temperature speeds up the painting process.

Updated Technical Data Sheet (TDS) and Safety Data Sheet (SDS) and our general conditions of sales are available at [www.nor-maali.fi](http://www.nor-maali.fi). In case of differences in information: the order of priority of information is TDS and SDS over any other information.



## NORECRYL 50

### MACHINERY AND EQUIPMENT GENERAL STEEL STRUCTURES

#### CORROSION RESISTANCE WITHOUT ISOCYANATE

VOLUME SOLIDS	65 %
VOC	300 G/L
MIXING RATIO	6:1
POT-LIFE	3.5 H
COLOURS	RAL AND NCS S
FINISH	SEMI GLOSS
<b>CORROSIVITY CATEGORY</b>	
SINGLE-COAT	C2 – C4
DURABILITY RANGE	120 µm – C4 M
TOPCOAT	C5

#### More information in the TDS

# NORMAALI

## ESTONIA

Oü Nor-Maali  
Vana-Narva mnt 5c,  
Maardu  
74114 Estonia

Tel. +372 600 3948  
[tellimus@nor-maali.ee](mailto:tellimus@nor-maali.ee)

## SLOVAKIA

Nor-Maali s.r.o.  
Senecká cesta 18  
821 04 Bratislava

Tel. +421 903 210 259  
[sales@nor-maali.sk](mailto:sales@nor-maali.sk)

## SWEDEN

Nor-Maali Group AB  
Varggatan 23  
749 40 Enköping

Tel. +46 70 537 6404  
Tel. +46 70 537 6414  
[forsaljning@normaali.se](mailto:forsaljning@normaali.se)