

EPOCOAT AQUA PRIMER

Environmentally friendly water-borne epoxy primer for demanding anti-corrosion painting

When a first-class corrosion resistance is required, **Epocoat Aqua Primer** is the right choice. This water-borne epoxy primer offers more environmentally friendly corrosion protection even in challenging industrial sites where the criteria for durability are high.

WHY TO CHOOSE EPOCOAT AQUA PRIMER?



GREENER CHOICE

Water-borne option to enhance work safety.



SUPERIOR DURABILITY

Excellent corrosion resistance as a primer and in a coating system.



USER FRIENDLY PRODUCT

Excellent spraying properties. Forms a smooth surface for topcoat.



FAST DRYING

Dries fast and is soon to be over-coated also at lower temperatures.

NORMAALI



+358 (0) 3 874 650



sales@nor-maali.fi



Vanhatie 20
15240 Lahti, Finland



Nor-maali.fi

FIRST-CLASS CORROSION RESISTANCE

Epocoat Aqua Primer is a water-borne epoxy primer that combines first-class technical properties and environmental friendliness.

Epocoat Aqua Primer is designed to be used as a primer in corrosion classes C2-C5. The product can be used with both water-borne and solvent-based (hybrid systems) topcoats. Two layer paint system Epocoat Aqua Primer + Norepox Aqua DTM reaches the corrosion class C5M with a total paint film of 180 µm.

Fast drying primer

Epocoat Aqua Primer dries quickly. The primer can be overcoated with same type of paint after three hours and with polyurethane coatings after four hours (+23 °C). A paint system with corrosion class C5M can be painted during one work shift.

Safer choice for industrial painting

Epocoat Aqua Primer is designed for more responsible painting, taking into account the technical properties. Due to the low VOC content, Epocoat Aqua Primer is a safer option for both the environment and the user.

Updated Technical Data Sheet (TDS) and Safety Data Sheet (SDS) and our general conditions of sales are available at www.nor-maali.fi. In case of differences in information: the order of priority of information is TDS and SDS over any other information.



EPOCOAT AQUA PRIMER

GENERAL STEEL STRUCTURES MACHINERY AND EQUIPMENT

FIRST-CLASS CORROSION PROTECTION FOR PAINT SYSTEMS

VOLUME SOLIDS	47 %
VOC	55 G/L
MIXING RATIO	5:1
POT-LIFE	5 H
COLOUR	GREY (NCS S3500-N)
FINISH	SEMI MATT
CORROSIVITY CATEGORY	
PAINT SYSTEMS	C2 – C5

More information in the TDS

NORMAALI

ESTONIA

Oü Nor-Maali
Vana-Narva mnt 5c,
Maardu
74114 Estonia

Tel. +372 600 3948
tellimus@nor-maali.ee

SLOVAKIA

Nor-Maali s.r.o.
Senecká cesta 18
821 04 Bratislava

Tel. +421 903 210 259
sales@nor-maali.sk

SWEDEN

Nor-Maali Group AB
Varggatan 23
749 40 Enköping

Tel. +46 70 537 6404
Tel. +46 70 537 6414
forsaljning@normaali.se