

SOLVENT-BASED SEMI GLOSS POLYURETHANE COATING

DIRECT-TO-METAL

TOPCOAT

NORMADUR 65 HS

Flexible direct-to-metal polyurethane coating for corrosion protection

Normadur 65 HS is the safe choice for anti-corrosion painting. This flexible polyurethane topcoat and single-coat protects against UV radiation and corrosion, and is also suitable to be used as maintenance coating on old paint surfaces.

WHY TO CHOOSE NORMADUR 65 HS?



DURABLE SURFACE

Corrosion resistant
direct-to-metal coating.



FLEXIBLE

Good impact resistance,
less need for touch-up
painting.



EASY TO SPRAY

High film thicknesses
are also possible.



MAINTENANCE COATING

Good adhesion on old
paint surfaces.

NORMAALI



+358 (0) 3 874 650



sales@nor-maali.fi



Vanhatie 20
15240 Lahti, Finland



Nor-maali.fi

DURABLE SURFACE WITH NORMADUR 65 HS SINGLE-COAT

Normadur 65 HS direct-to-metal coating protects against UV radiation and corrosion. The product is used in corrosion classes C2-C3 as a single-coat and in higher corrosion classes as a topcoat.

Flexible paint film

Normadur 65 HS forms a very flexible paint film, which guarantees a good impact resistance. The need for touch-up painting in product painting is reduced.

Easy to spray

With Normadur 65 HS high film thicknesses can be sprayed at one time, because the product has a high sagging limit. For multi-shaped objects, this makes the painting process easier.

Shades that cover well

Normadur 65 HS is available in three colored bases: yellow, red and orange. The paint therefore gives very opaque shades, which can also be painted as a single-coat.

Maintenance coating

Normadur 65 HS is also suitable to be used as a maintenance coating. It has good adhesion to old paint surfaces.

Updated Technical Data Sheet (TDS) and Safety Data Sheet (SDS) and our general conditions of sales are available at www.nor-maali.fi. In case of differences in information: the order of priority of information is TDS and SDS over any other information.



NORMADUR 65 HS

**MACHINERY AND EQUIPMENT
GENERAL STEEL STRUCTURES**

CORROSION RESISTANT GLOSS RETAINING COATING

VOLUME SOLIDS	65 %
VOC	310 G/L
MIXING RATIO	4:1
POT-LIFE	1 H
COLOURS	RAL, NCS S, KY AND SSG
FINISH	SEMI GLOSS
CORROSIVITY CATEGORY	
SINGLE-COAT	C2 – C3
DURABILITY RANGE	120 µm – C3 M
TOPCOAT	C2 – C5

More information in the TDS

NORMAALI

ESTONIA

Oü Nor-Maali
Vana-Narva mnt 5c,
Maardu
74114 Estonia

Tel. +372 600 3948
tellimus@nor-maali.ee

SLOVAKIA

Nor-Maali s.r.o.
Senecká cesta 18
821 04 Bratislava

Tel. +421 903 210 259
sales@nor-maali.sk

SWEDEN

Nor-Maali Group AB
Varggatan 23
749 40 Enköping

Tel. +46 70 537 6404
Tel. +46 70 537 6414
forsaljning@normaali.se