

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Date of revision: 03.01.2024 Date of previous issue: 26.09.2023 Version number 2 (replaces version 1)

Page 1/11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Normathane 50 FD Comp. A
- · UFI: M0H8-T0XJ-800K-WCE3
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use Coating
- Product category PC9a Coatings and paints, thinners, paint removers
- Application of the substance / the mixture

2-comp. polyurethane paint, Comp. A Uses in Coatings - Industrial use Uses in Coatings - Professional use

- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Nor-Maali Oy

Vanhatie 20, 15240 Lahti, FINLAND

- · Further information obtainable from: MSDS (Nor-Maali Oy) tel.+358 3 874 650, sds@nor-maali.fi
- · 1.4 Emergency telephone number: Contact National Poison Center

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Product definition: mixture

· Classification according to Regulation (EC) No 1272/2008



GHS02 flame

H226 Flammable liquid and vapour. Flam. Liq. 3



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Sens. 1 STOT SF 3

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms







GHS02

GHS07

GHS09

Signal word Warning

· Hazard-determining components of labelling:

n-butyl acetate

Pentaerythritol tetrakis(3-mercaptopropionate)

Phosphorous acid, triisodecyl ester

isobutyl methacrylate

(Contd. on page 2)



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Date of revision: 03.01.2024 Date of previous issue: 26.09.2023 Version number 2 (replaces version 1)

Trade name: Normathane 50 FD Comp. A

(Contd. of page 1)

Page 2/11

· Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

· Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	10 - 25%
CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-	titanium dioxide Carc. 2, H351	
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	2.5 - 10%
CAS: 7575-23-7 EINECS: 231-472-8 Reg.nr.: 01-2119486981-23-	Pentaerythritol tetrakis(3-mercaptopropionate) Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); Acute Tox. 4, H302; Skin Sens. 1A, H317	< 0.4%
CAS: 77745-66-5 EINECS: 278-758-9 Reg.nr.: 01-2119487302-40-	Phosphorous acid, triisodecyl ester Skin Sens. 1, H317	< 0.4%
CAS: 77-99-6 EINECS: 201-074-9 Reg.nr.: 01-2119486799-10-	propylidynetrimethanol Repr. 2, H361fd	< 0.2%
CAS: 97-86-9 EINECS: 202-613-0 Reg.nr.: 01-2119488331-38-	isobutyl methacrylate Flam. Liq. 3, H226; Skin Irrit. 2, H315; Skin Sens. 1B, H317; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 10 %	< 0.2%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Never give anything by mouth or induce vomiting to an unconscious person or a person who has convulsions.

After inhalation:

Remove person exposed to excessive solvent concentrations to fresh air, keep patient warm and at rest. If breathing is irregular, call national emergency number, if needed start giving artificial respiration and seek medical advice.

(Contd. on page 3)



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Date of revision: 03.01.2024 Date of previous issue: 26.09.2023 Version number 2 (replaces version 1)

Trade name: Normathane 50 FD Comp. A

(Contd. of page 2)

Page 3/11

· After skin contact:

Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

· After eye contact:

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.

After swallowing:

If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

- · Information for doctor: Treatment according to symptoms.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: Alcohol resistant foam, CO₂, powders, water spray.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters

Evacuate people from danger area and deny access to area. Remove containers from danger area and try to cool containers which cannot be removed safely. This material is toxic to aquatic life with long lasting effects. Fire water contamined with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Protective equipment: Compressed air respirator and protective clothing.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

· 6.2 Environmental precautions:

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material (sand, peat or other absorbent material). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original

(Contd. on page 4)



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Date of revision: 03.01.2024 Date of previous issue: 26.09.2023 Version number 2 (replaces version 1)

Trade name: Normathane 50 FD Comp. A

(Contd. of page 3

Page 4/11

one. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Information about fire - and explosion protection:

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in accordance with local regulations. Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. Keep away from: oxidising agents, strong alkalis, strong acids. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not empty into drains.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

Ingredien	its with limit values that require monitoring at the workplace:	
	n-butyl acetate	
HTP (Finla	and) Short-term value: 725 mg/m³, 150 ppm	
100 05 0	Long-term value: 240 mg/m³, 50 ppm	
	2-methoxy-1-methylethyl acetate	
HIP (Finia	and) Short-term value: 550 mg/m³, 100 ppm Long-term value: 270 mg/m³, 50 ppm	
	skin	
DNELs		
123-86-4 r	n-butyl acetate	
Dermal	DNEL 7 mg/kg bw/day (Workers - Long-term systemic effects)	
Inhalative	DNEL 480 mg/m3 (Workers - Long-term systemic effects)	
108-65-6 2	2-methoxy-1-methylethyl acetate	
Dermal	DNEL 796 mg/kg bw/day (Workers - Long-term systemic effects)	
	DNEL 275 mg/m3 (Workers - Long-term systemic effects)	
	Pentaerythritol tetrakis(3-mercaptopropionate)	
	DNEL 7 mg/kg bw/day (Workers - Long-term systemic effects)	
	DNEL 4.93 mg/m3 (Workers - Long-term systemic effects)	
	-5 Phosphorous acid, triisodecyl ester	
Dermal	DNEL 6.25 mg/kg bw/day (Workers - Long-term systemic effects)	
	DNEL 767.5 μg/kg bw/day (Workers - Long-term local effects)	
	DNEL 4.4 mg/m3 (Workers - Long-term systemic effects)	
	ropylidynetrimethanol	
Dermal	DNEL 940 μg/kg bw/day (Workers - Long-term systemic effects)	
	DNEL 3.3 mg/m3 (Workers - Long-term systemic effects)	
	sobutyl methacrylate	
Dermal	DNEL 5 mg/kg bw/day (Workers - Long-term systemic effects)	
Inhalative	DNEL 415.9 mg/m3 (Workers - Long-term systemic effects)	
	409 mg/m3 (Workers - Long-term local effects)	

(Contd. on page 5)



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Date of revision: 03.01.2024 Date of previous issue: 26.09.2023 Version number 2 (replaces version 1)

Page 5/11

Trade name: Normathane 50 FD Comp. A

	(Contd. of page 4)			
	0.018 mg/L (Marine water)			
	35.6 mg/L (Sewage treatment)			
PNEC	0.981 mg/kg dwt (Fresh water sediment)			
	0.0981 mg/kg dwt (Marine water sediment)			
	0.0903 mg/kg dwt (Soil)			
108-65	-6 2-methoxy-1-methylethyl acetate			
PNEC	0.635 mg/L (Freshwater)			
	0.0635 mg/L (Marine water)			
	100 mg/L (Sewage treatment)			
PNEC	3.29 mg/kg dwt (Fresh water sediment)			
	0.329 mg/kg dwt (Marine water sediment)			
PNEC	0.29 mg/kg (Soil)			
7575-2	3-7 Pentaerythritol tetrakis(3-mercaptopropionate)			
PNEC	2.39 mg/L (Sewage treatment)			
PNEC	0.018 mg/kg dwt (Fresh water sediment)			
	0.00181 mg/kg dwt (Marine water sediment)			
PNEC	0.00337 mg/kg (Soil)			
PNEC	0.42 μg/L (Freshwater)			
	0.042 μg/L (Marine water)			
	9 isobutyl methacrylate			
PNEC	10 mg/L (Sewage treatment)			
PNEC	5.89 mg/kg dwt (Fresh water sediment)			
	0.589 mg/kg dwt (Marine water sediment)			
PNEC	1.16 mg/kg (Soil)			
PNEC	21 μg/L (Freshwater)			
	2.1 μg/L (Marine water)			

Additional information:

The information is based on the valid lists at the time of manufacture (Finland 654/2020).

- 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the HTP, suitable respiratory protection must be worn.

Respiratory protection:

If ventilation is insufficient or if workers are exposed to concentrations above the exposure limit they must use half- or full mask with gas filter A (brown, organic substances), and when grinding P2 (IIb) -type dust filter. Mask with combined filter (gas & dust) A2-P2 must be used when spraying. In the continuous long-term work it is recommended to use motored air protector or separative protector (fresh air hood or compressed air hood or such).

· Hand protection



Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Wear suitable gloves tested to EN374.

May be used, gloves(breakthrough time) 4 - 8 hours: butyl rubber, nitrile rubber

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Date of revision: 03.01.2024 Date of previous issue: 26.09.2023 Version number 2 (replaces version 1)

Page 6/11

(Contd. of page 5)

Trade name: Normathane 50 FD Comp. A

· Eye/face protection



Tightly sealed goggles

The eye flushing device should be located near the the paint work area.

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Colourful
Strong
Colour threshold:

· Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

 \cdot Boiling point or initial boiling point and boiling

range 124 - 128 °C (123-86-4 n-butyl acetate)

· Flammability Flammable.

Lower and upper explosion limit

 Lower:
 1.2 Vol % (123-86-4 n-butyl acetate)

 Upper:
 7.5 Vol % (123-86-4 n-butyl acetate)

· Flash point: 27 °C

Auto-ignition temperature: 370 °C (123-86-4 n-butyl acetate)

Decomposition temperature: Not determined.

• **pH** Mixture is non-soluble (in water).

· Viscosity:

· Kinematic viscosity at 40 °C > 20.5 mm²/s

Dynamic: Not determined. Solubility

water: Fully miscible.
 Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C: 10.7 hPa (123-86-4 n-butyl acetate)

Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

9.2 Other information

· Appearance:

· Form: Fluid

Important information on protection of health and

environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Change in condition

• Evaporation rate Not determined.

Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

• Flammable liquids Flammable liquid and vapour.

Flammable solids Void

(Contd. on page 7)



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Date of revision: 03.01.2024 Date of previous issue: 26.09.2023 Version number 2 (replaces version 1)

Page 7/11

Trade name: Normathane 50 FD Comp. A

		(Contd. of page 6)
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability

Oral

LD50

9,590 mg/kg (rat)

Thermal decomposition / conditions to be avoided:

In confined or poorly ventilated spaces solvent may form an explosive mixture with air.

· 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 · Acute toxicity Based on available data, the classification criteria are not met. · LD/LC50 values relevant for classification: 123-86-4 n-butyl acetate 10,760 mg/kg (rat) (OECD 423) Oral LD50 Dermal LD50 > 14,112 mg/kg (rabbit) Inhalative LC50/4 h > 21.1 mg/l (rat) 13463-67-7 titanium dioxide Oral LD50 > 5,000 mg/kg (rat) > 10,000 mg/kg (rabbit) Dermal LD50 108-65-6 2-methoxy-1-methylethyl acetate Oral LD50 6,190 mg/kg (rat) LD50 Dermal > 2,000 mg/kg (rat) 7575-23-7 Pentaerythritol tetrakis(3-mercaptopropionate) LD50 1,000 mg/kg (rat) Oral Inhalative LC50/4 h 3.363 mg/l (rat) 77745-66-5 Phosphorous acid, triisodecyl ester > 2,000 mg/kg (rat) Oral LD50 Dermal LD50 5,000 mg/kg (rabbit) Inhalative LC50/4 h 12,600 mg/l (rat) 77-99-6 propylidynetrimethanol Oral LD50 14,700 mg/kg (rat) Dermal LD50 10,000 mg/kg (rabbit) Inhalative LC50/4 h 850 mg/l (rat) 97-86-9 isobutyl methacrylate

(Contd. on page 8)



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Date of revision: 03.01.2024 Date of previous issue: 26.09.2023 Version number 2 (replaces version 1)

Trade name: Normathane 50 FD Comp. A

(Contd. of page 7)

Page 8/11

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Other information (about experimental toxicology):

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Swallowing may cause nausea, diarrhea, vomiting, gastro-intestinal irritation and chemical pneumonia.

- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

	· · · · · · · · · · · · · · · · · · ·	
· Aquatic toxicity:		
123-86-4 n-butyl acetate		
72-h EC50	647.7 mg/L (Desmodesmus subspicatus)	
48-h EC50	44 mg/L (Daphnia magna)	
96-h LC50	18 mg/L (Pimephales promelas) (OECD 203)	
NOEC	200 mg/L (Desmodesmus subspicatus)	
13463-67-7	13463-67-7 titanium dioxide	
96-h LC50	10,000 mg/L (Fish) (OECD 203)	
108-65-6 2-methoxy-1-methylethyl acetate		
48-h EC50	-h EC50 500 mg/L (Daphnia magna)	
96-h LC50	100 - 180 mg/L (Fish)	
96-h EC50	1,000 mg/L (Algae)	
7575-23-7 Pentaerythritol tetrakis(3-mercaptopropionate)		
72-h EC50	0.65 mg/L (Algae)	
48-h EC50 0.35 - 0.85 mg/L (Daphnia magna)		
96-h LC50	0.034 - 0.42 mg/L (Fish)	
77-99-6 pro	ppylidynetrimethanol	
72-h EC50	1 mg/L (Algae)	
48-h EC50 13 mg/L (Daphnia magna)		
96-h LC50 1 - 10 mg/L (Fish)		
97-86-9 iso	butyl methacrylate	
72-h EC50	16 mg/L (Algae)	
48-h EC50 29 mg/L (Daphnia magna)		
96-h LC50	20 mg/L (Fish)	

12.2 Persistence and degradability

Biodegradability:

2-methoxy-1-methylethyl acetate: readily n-butyl acetate: 90 %, 28 d -> readily

12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 9)



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Date of revision: 03.01.2024 Date of previous issue: 26.09.2023 Version number 2 (replaces version 1)

Trade name: Normathane 50 FD Comp. A

(Contd. of page 8)

Page 9/11

- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Do not allow to enter drains or watercourses. Material and/or container must be disposed of as hazardous waste.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- Recommendation:

Empty, dry paint containers (hole made to the bottom) should be taken to collection centres for metallic paint packages. If this collecting/recycling centre doesn't exist, containers can be taken to a local dump pit. For more information contact your local waste disposal authorities or paint deliverer.

SECTION 14: Transport informat	tion
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR · IMDG	PAINT, ENVIRONMENTALLY HAZARDOUS PAINT, MARINE POLLUTANT Marine Pollutant Chemical: Pentaerythritol tetrakis(3- mercaptopropionate) PAINT
· 14.3 Transport hazard class(es)	
·ADR	
· Class	3 Flammable liquids.
· IMDG, IATA	
· Class	3 Flammable liquids.
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substance Pentaerythritol tetrakis(3-mercaptopropionate)
	Pentaerythritol tetrakis(3-mercaptopropionate) (Contd. on page

iliu. Oli page li



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Date of revision: 03.01.2024 Date of previous issue: 26.09.2023 Version number 2 (replaces version 1)

Page 10/11

Trade name: Normathane 50 FD Comp. A

	(0, 11, 6
	(Contd. of page
· Special marking (ADR):	The environmental hazardous mark is only applicable fo packages containing more than 5 litres of liquids. Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
· 14.7 Maritime transport in bulk according to IN instruments	Not applicable.
· Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

(Contd. on page 11)



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Date of revision: 03.01.2024 Date of previous issue: 26.09.2023 Version number 2 (replaces version 1)

Page 11/11

Trade name: Normathane 50 FD Comp. A

(Contd. of page 10) H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H400 Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. H410 EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 26.09.2023 · Version number of previous version: 1 · Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Skin Sens. 1B: Skin sensitisation - Category 1B Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2 * Data compared to the previous version altered.

GB